

Chapel Light

A classic handmade brick you'll see on cottages, farmhouses and converted barns across the shire counties. Lightly weathered for a textured appearance, Chapel Light bricks are a superb match for conservation projects and can be used as the backbone of new developments.

FIND OUT MORE ABOUT OUR BRICK RANGE

T: 0161 641 3579

W: www.manchesterbrick.com



PRODUCT TECHNICAL INFORMATION

MANCHESTER BRICK CODE	MBS00060 / MBS00630 / MBS01460
MANUFACTURED TO	BS EB 771-1
CONFIGURATION	Frogged
COLOUR	Orange and Red
APPEARANCE	Traditional
SIZE	
Metric	65mm x 215mm x 102.5mm 68mm x 228mm x 110mm 73mm x 228mm x 110mm
PACK SIZE	650 / 525 / 500
INDIVIDUAL DRY BRICK WEIGHT	2kg / 2.3kg / 2.5kg

TECHNICAL PROPERTIES TO BS EN 771-1

TYPE	High Quality Coal Fired Handmades
GROSS DRY DENSITY (KG/M³ /TOLERANCE)	1,650kg/m ³ (D1)
COMPRESSIVE STRENGTH	>=20N/mm ²
THERMAL CONDUCTIVITY*	0.79 W/m.k [λ10,dry]
SIZE TOLERANCE (MEAN/RANGE)	T1/R1
WATER ABSORPTION	<=15% _m /md
INITIAL RATE OF WATER ABSORPTION (KG/(M² MIN))	3.9/m ² .min (IW3)
REACTION TO FIRE	A1
ACTIVE SOLUBLE SALTS	S2
DURABILITY DESIGNATION	F2



Technical data correct at time of issue. Individual dry brick weights can vary and are for guidance only. Any questions regarding this data should be referred to the Manchester Brick Technical Department. Due to the limitations of screen and print colour representation of product images it is advised that brick samples are viewed prior to ordering.

