

Smooth Red

Extruded wirecut bricks with a glazed finish, Smooth Reds are a popular facing material.

Their uniform appearance makes them a favourite for new builds and extensions, especially in the Midlands and the North, where their colour closely matches much of the existing housing stock.

FIND OUT MORE ABOUT OUR BRICK RANGE

T: 0161 641 3579

W: www.manchesterbrick.com



PRODUCT TECHNICAL INFORMATION		TECHNICAL PROPERTIES TO BS EN 771-1	
MANCHESTER BRICK CODE	MBS01300	TYPE	Wirecut
MANUFACTURED TO	BS EN 771-1	GROSS DRY DENSITY (KG/M ³ /TOLERANCE)	2300kg/m ³ (D1)
CONFIGURATION	Vertically Perforated 26% Voids	ACTIVE SOLUBLE SALTS	S2
COLOUR	Red	COMPRESSIVE STRENGTH	>=90N/mm ²
APPEARANCE	Smooth	THERMAL CONDUCTIVITY*	<0.47 W/m.k
SIZE Metric	65mm x 215mm x 102.5mm 73mm x 215mm x 102.5mm	SIZE TOLERANCE (MEAN/RANGE)	T2/R2
PACK SIZE	512 / 464	DURABILITY DESIGNATION	F2
INDIVIDUAL DRY BRICK WEIGHT	2.4kg / 2.6Kg	WATER ABSORPTION	<=8% _m /md
		INITIAL RATE OF WATER ABSORPTION (KG/(M ² MIN))	1.0 - 4.0kg/m ² .min (IW3)
		REACTION TO FIRE	A1



Technical data correct at time of issue. Individual dry brick weights can vary and are for guidance only. Any questions regarding this data should be referred to the Manchester Brick Technical Department. Due to the limitations of screen and print colour representation of product images it is advised that brick samples are viewed prior to ordering.

