## Moorland Black Sandface

## FIND OUT MORE ABOUT OUR BRICK RANGE

T: 0161 641 3579

W: www.manchesterbrick.com

PRODUCT TECHNICAL INFORMATION		
MANCHESTER BRICK CODE	MBS02820 MBS02800	
MANUFACTURED TO	BS EN 771-1	
CONFIGURATION	Vertically Perforated 26% Voids	
COLOUR	Black	
APPEARANCE	Sandfaced	
SIZE Metric	73mm x 215mm x 102.5mm 65mm x 215mm x 102.5mm	
PACK SIZE	464 / 512	
INDIVIDUAL DRY BRICK WEIGHT	2.6kg / 2.4kg	

TECHNICAL PROPERTIES TO BS EN 771-1		
ТҮРЕ	Wirecut	
GROSS DRY DENSITY (KG/M <sup>3</sup> /TOLERANCE)	2300kg/m <sup>3</sup> (D1)	
ACTIVE SOLUBLE SALTS	S2	
COMPRESSIVE STRENGTH	$\geq 90N/mm^2$	
THERMAL CONDUCTIVITY*	<0.47 W/m.k	
SIZE TOLERANCE (MEAN/RANGE)	T2/R2	
DURABILITY DESIGNATION	F2	
WATER ABSORPTION	≤7%m/md	
INITIAL RATE OF WATER ABSORPTION (KG/(M <sup>2</sup> MIN))	1.0-4.0kg/m².min (IW3)	
REACTION TO FIRE	A1	

guidance only. Any questions regarding this data should be referred to the Manchester Brick Technical Department. Due to the limitations of screen and print colour representation of product images it is advised that brick samples are viewed prior to ordering.







